

PowerStation Protective Overlay Installation

Background

Protective overlays are used on PowerStations to protect the screen of the unit from debris and make it easier to clean.

CTC sells clear and anti-glare protective overlays in packages of five (5) to fit any display type. To order additional overlays, refer to your CTC price list, or contact your CTC equipment supplier for current model numbers and pricing.

Removing an Existing Overlay

Follow these steps to remove an overlay from a PowerStation:

1. Grasp the small tab in the lower left corner of the PowerStation's display.
2. Pull gently away from the unit until the overlay is completely removed.
3. Wash any residual adhesive off the display with a small amount of lighter fluid and a cloth.

Applying an Overlay

Follow these steps to apply an overlay to a PowerStation:

1. Turn the PowerStation OFF, and make sure the faceplate is clean.
2. Remove an overlay from the package.
3. Peel the clear protective skin from the side of the overlay with the laminating adhesive.

Caution Avoid touching the adhesive side of the overlay; it scratches easily.

4. Remove the backing from the adhesive; begin peeling at the small notch at the top center of the overlay.
5. Place the overlay on the PowerStation with the adhesive side toward the faceplate. Place the overlay inside the bezel with the tab in the lower left corner.

PowerStation Protective Overlay Installation

6. Press along the edges of the overlay to secure it to the faceplate.
7. Remove the protective skin from the front of the overlay.
8. Turn the PowerStation ON, and resume operation.